



AS 901 SM FLAIL MOWER



Steering and braking clutch

Folding bar with lateral and height adjustment

2-cylinder B+S engine with oil and fuel pump

AS 901 SM

Pendulum-mounted flail mowing mechanism

Stone guard flaps

Agricultural tread twin tires

Stone impact protection

Swivelling front wheels

FOR USE IN:



Meadows



Long meadow grass



Mulching & shredding



Slopes



Scrub/woodland



Uneven terrain



Professional

YouTube



TOP



Technical specifications ▶

RUGGED FLAIL MOWING MECHANISM

Durable steel cutter housing with 26 high-speed Y flails. Two-stage safety barriers provide protection for operator and bystanders.

EASY-TO-USE STEERING BRAKE

Independent steering brakes provide precise and effortless control.

HIGH WORK RATE

Ideal for mowing and mulching in challenging areas, even on slopes.

AGILE AND WELL-BALANCED

Stable, lightweight construction with double-skinned mower hood and robust frame. A low center of gravity provides stability on slopes.

TWIN TIRES FOR EXCELLENT TRACTION

Wide twin tires with agricultural tread guarantee exceptional traction on slopes and in ditches.

Recommended retail price





AS 901 SM FLAIL MOWER
HIGH WORK RATE, PERFECT HANDLING
PERFORMS ON SLOPES

as-america.com

AS 901 SM TECHNICAL SPECIFICATIONS

Cutting width:	36 inches
Engine:	B+S Two-cylinder, 4-stroke engine Vanguard, V-Twin, 29.3 cu in
Rated power:	10.7 kW (15.8 HP) at 3,500 rpm
Maximum engine power:	11.9 kW (16.0 HP) at 3,600 rpm
Wheel drive speed:	Rear-wheel drive 0.7 – 2.5 mph, (5-speed) reverse 1.1 mph
Special characteristics:	5-speed gearbox with differential lock and steering brake
Cutting height adjustment:	Central 0.8 – 3.9 inches, 6 levels
Max. work rate yd²/h:	4,306
Weight:	502 lb
Operating dimensions:	L 87 / W 41 / H 41 inches

YouTube



Errors and changes are reserved. Images can be similar. Version: 2017-09-01

